



Multi-channel Voltage Detection

NOVX MODEL 3352/3362

Simco-Ion's Novx brand of Passive (Model 3352) and Active (Model 3362) Multi-fan Closed-loop Ionizer Controllers provide the capability to simultaneously detect, measure, record and monitor electrostatic voltages in multiple locations. The versatile antennas used with these systems allow their use in a variety of applications including monitoring sensitive workstations, in-tool voltages, or ionizer performance with the option of closed-loop control to select ionizer products. Up to 3 sensors can be connected to an individual instrument. This multi-channel capability provides a cost-effective monitoring solution for multiple areas or ionizers. Data input is actively monitored and logged with time stamps using Calibrator_Reader. The instruments have user settable thresholds and alarm levels that provide a proactive safeguard for critical areas when interfaced to an alarm output. Out of range conditions can trigger a remote alarm light or audible alarms, shut down a critical process, or make adjustments to an ionizing fan.

Features



- Digital, microprocessor-based controllers, multi-channel, digital I/O, auxiliary I/O, local addressability, RS-485/Modbus or Ethernet data output
- Passive (unpowered) and active antenna configurations
- Precision resolution
- Programmable closed-loop control for up to 3 SSDC ionizer fans or a 3-fan blower
- Programmable alarm set-points with tool shutdown option
- Voltage/polarity displays, local red/green LEDs each channel


Benefits

- Provides easy integration, cost/performance advantages over other monitoring solutions, direct communication to other Novx instruments or to a tool controller.
- Wide variety of applications: monitor voltage at distances and ionizer balance; perform In Situ decay testing without the added expense of a CPM
- Measure and record voltage down to 0.1V
- Enable closed-loop feedback control to select ionizers based on balance or decay test results
- Reduce process variations, decrease scrap/rework, and improve process yields
- Visual indicators at the instrument



Specifications

	Model 3352	Model 3362
Input Voltage	24 VDC	24 VDC
Capacity	1, 2 or 3 fans	1, 2 or 3 fans
Reporting Range	0 to $\pm 5000V$	0 to $\pm 150V$
Accuracy	0.5V for $<20V$; $\pm 5\%$ for $>20V$	1V for $<20V$; $\pm 5\%$ for $>20V$
Audible Alarm Set-points	$\pm 0.5V$ (min)	$\pm 1V$ (min)
LEDs/Channel	Red/green or alarm indicator	Red/green or alarm indicator
Alarm Set-point	Programmable	Programmable
Zero Set-point	Programmable	Programmable
Aux Out	Open collector	Open collector
Output Signals	Digital	Digital
Antennas	up to 3 channels	up to 3 channels
Decay Testing	NA	up to 3 channels
Communication	Novx Com RS-485/Modbus, Ethernet	Novx Com RS-485/Modbus, Ethernet
Digital Display/Channel	4-Digit	4-Digit
Dimensions	2.0W x 6.8D x 6.5H in. (5.1W x 17.3D x 16.5H cm)	2.0W x 6.8D x 6.5H in. (5.1W x 17.3D x 16.5H cm)
Weight	2.1 lb (0.95 kg)	2.2 lb (1 kg)
Enclosure	Stainless Steel	Stainless Steel
Warranty	Two-year limited warranty	Two-year limited warranty
Certifications		

Power Adapter 14-21327	
Input Voltage	100-240 VAC 50/60 Hz
Output Voltage	24 VDC, 30 W
Dimensions	4H x 1.9W x 1.1D in. (103 x 42 x 29 mm)
Weight	5 oz (140 g)
Certifications	

Ordering Information

91-3352-01	Novx 3352 Passive Multi-fan Closed-loop Ionizer Controller
91-3362-01	Novx 3362 Active Multi-fan Closed-loop Ionizer Controller
32-0220	Mounting Bracket, "L" (2 pcs per controller)
33-0520-5	Passive Antenna, 1.75" x 1" Tall with SMA-to-SMA Cable (5 ft)
33-0504	Passive Antenna, 1.75" x 4" Tall with SMA-to-SMA Cable (5 ft)
33-0510-xx	Passive Antenna, 1" Tall with SMA-to-SMA X ft Cable (xx = 5 or 15)
33-0509-15	Active Antenna Assembly, 5" x 0.5" Tall with 15 ft Triaxial Cable
33-0523-XX	Active Antenna Assembly, 1.75" x 1" Tall with X ft Triaxial Cable (X = 5 or 20)
33-0507-5	Active Antenna Assembly, 1.75" x 4" Tall with 5 ft Triaxial Cable
14-21327	100-240 VAC to 24 VDC Power Adapter

Calibration

Instruments are shipped calibrated and certified. Calibration must be validated annually to meet ISO certification compliance requirements.

Applications

The **Novx 3352 Passive Multi-fan Closed-loop Controller** connects with passive antennas to detect low level voltage change and ion current ($\leq 400V$) with sensitivity down to 1V. Antenna connection configurations:

- Monitor voltages on moving targets
- Monitor ionizer balance
- Provide closed-loop control to ionizer fans
- Distinguish the proximity of voltages from steady state DC ionizer signals

The **Novx 3362 Active Multi-fan Closed-loop Controller** connects to active antennas, providing similar voltage and ion current detection capability as the 3352 with the addition of decay tests. The powered antenna acts as a charged plate monitor (CPM) to periodically measure ionizer discharge times at programmable frequencies. A "Decay Test" button is provided on the front panel of the 3362 for manually initiating an ionizer decay test.

Antenna connection configurations:

- Monitor voltages on moving targets
- Monitor ionizer balance
- Distinguish the proximity of field from steady state DC ionizer signals
- Perform decay testing automatically or on command

Special Features

Both the Novx 3352 and 3362 feature a front panel which have an LCD screen that displays the voltage and alarm status of each of the three channels in real-time. Each interfaces with the Novx Calibrator_Reader for full setup, visual monitoring, and logging capability. Files can be exported for Excel graphing and analysis. These instruments can operate as stand-alone systems and interface to the process for initiated response.



SIMCO IONTM
An ITW Company

DS-3352 3362_V1 - 3/17
© 2017 Simco-Ion
All rights reserved.

Simco-Ion

Technology Group
1601 Harbor Bay Pkwy, Ste 150
Alameda, CA 94502

Tel: +1 (800) 367-2452 (in USA)
Tel: +1 (510) 217-0600

ioninfo@simco-ion.com
www.simco-ion.com